

LAMELLARE CHIMNEY CAP

ART. 1300



Usage of the product:

The Lamellare chimney cap is a modern compact flue terminal which also has a pleasing appearance. It guarantees good emission of combustion fumes and also functions well under adverse weather conditions. On request, it is possible to have a version which can be 'inspected'. In this case, the top element is not welded on but is fixed into place by an attachment and steel bolts, thus enabling the flue to also be inspected from above without having to remove the terminal.

Installation instructions:

Install on the terminal part of the chimney flue. Fix by means of a flue clamp. Do not use a silicon sealant only. Installation of the chimney cap must be carried out by qualified personnel.



STAINLESS
STEEL



COPPER

Available for Single Wall flue pipes, both male and female, and for Double Wall flue pipes 25mm insulation.

On request it is possible produce the cap for Double Wall with 50 mm insulation.

Conforms to UNI 7129/01 sez. 4-3-3 regulations regarding chimney caps.

EC Certifications in conformity with EN 1856-1 :
- Resistance to flow.

Art. 1300 - single wall

ø	80	100	120	130	140	150	160	180	200	220	250	300	350
H	180	215	215	220	220	230	230	270	270	270	310	350	390
A	130	150	180	180	200	200	230	230	250	300	300	350	400
hL	20	20	20	22	22	25	25	25	25	25	25	25	25
N°lam	3	4	4	4	4	4	4	5	5	5	6	7	7

Art. 1300 DP - double wall

ø	80/130	100/150	130/180	150/200	180/230	200/250	250/300	300/350	350/400
H	180	215	220	230	270	270	310	350	390
A	130	150	180	200	230	250	300	350	400
hL	20	20	22	25	25	25	25	25	25
N°lamelle	2	3	3	3	4	4	5	6	7

