

# MANTELLO CHIMNEY CAP

ART. 1270



STAINLESS  
STEEL



COPPER

## Usage of the product:

The Mantello chimney cap protects the smoke flue from infiltration by rain water and snow whilst allowing the free emission of smoke even in the presence of high wind.

## Installation instructions:

Install on the terminal part of the chimney flue. Fix by means of a flue clamp. Do not use a silicon sealant only. Installation of the chimney cap must be carried out by qualified personnel.

Available for Single Wall flue pipes, both male and female, and for Double Wall flue pipes 25 mm insulation. On request it is possible produce the cap for Double Wall with 50 mm inculation.

Conforms to UNI 7129/01 sez. 4-3-3 regulations regarding chimney caps.

EC certification in conformity with EN 1856-1:

- Resistance to flow.
- Technical conformity report "Chimney cap protecting from rain".

## Art. 1270 - single wall

Ø	80	100	120	130	140	150	160	180	200	220	250	300	350	400
H	240	240	240	240	260	260	280	280	320	340	340	400	400	418
A	185	185	220	220	260	260	260	300	310	370	420	470	530	610
Hf	165	165	165	165	200	200	200	200	250	250	250	310	310	410

## Art. 1270 DP - double wall

Ø	80/130	100/150	130/180	150/200	180/230	200/250	250/300	300/350	350/400
H	240	260	280	320	340	340	400	400	500
A	220	260	300	310	370	420	470	530	610
Hf	165	200	200	250	250	250	310	310	415

