

SEMPLICE CHIMNEY CAP

ART. 1250



Usage of the product:

The Semplice chimney cap is a particularly economical way of protecting the smoke flue against rain.

Installation instructions:

Install on the terminal part of the chimney flue. Fix by means of a flue clamp. Do not use a silicon sealant only. Installation of the chimney cap must be carried out by qualified personnel.

Available for Single Wall flue pipes, both male and female, and for Double Wall flue pipes 25 mm insulation. On request it is possible produce the cap for Double Wall with 50 mm insulation.

EC Certification in conformity with EN 1856-1 :
- Resistance to flow.



STAINLESS
STEEL



COPPER



GALVANIZED

Art. 1250 - single wall

ø	80	100	120	130	140	150	160	180	200	220	250	300	350	400
H	185	205	205	205	210	210	215	225	235	250	260	285	310	340
A	180	230	265	265	265	265	265	320	320	400	400	500	600	600
He	50	70	70	70	75	75	80	90	100	115	125	150	175	200

Art. 1250 DP - double wall

ø	80/130	100/150	130/180	150/200	180/230	200/250	250/300	300/350	350/400
H	195	200	215	225	250	250	275	300	320
A	265	265	320	320	400	400	500	600	600
He	70	75	90	100	110	125	150	175	200

