## **VEGA CHIMNEY CAP**

ART. 1255



COPPER

The Vega chimney cap is a

Usage of the product:

functional flue terminal which gives excellent protection against wind and rain. It is also particularly effective against snow and nesting birds. Installation instructions:

Install on the terminal part of the chimney flue. Fix by means of a flue clamp. Do not use a silicon sealant only. Installation of the chimney cap must be carried out by qualified personnel.

Available for Single Wall flue pipes, both male and female, and for Double Wall flue pipes 25mm insulation.


Conforms to UNI 7129/01 sez. 4-3-3 regulations regarding chimney caps.

EC Certifications in conformity with EN 1856-1 :

- Resistance to flow.
- Technical conformity report "Chimney cap protecting from rain" .


## Art. 1255 - single wall

ø	80	100	120	130	140	150	160	180	200	220	250	300
н	270	280	280	280	280	280	280	285	300	300	300	310
Α	230	230	230	320	320	320	320	320	400	400	500	500
Hf	110	110	110	110	110	110	110	110	110	110	110	110



## Art. 1255 DP - double wall

<ul> <li>Ø 80/130 100/150 130/180 150/200 180/230 200/250 250/300 300/350 350/40</li> <li>H 280 280 285 300 300 300 310 310 310 310</li> </ul>										
H 280 280 285 300 300 300 310 310 310	ø	80/130	100/150	130/180	150/200	180/230	200/250	250/300	300/350	350/400
	н	280	280	285	300	300	300	310	310	310
A 320 320 320 400 400 500 500 500 600	Α	320	320	320	400	400	500	500	500	600
Hf 110 110 110 110 110 110 110 110 110	Hf	110	110	110	110	110	110	110	110	110



14