

VENEZIA CHIMNEY CAP

ART. 1275



Usage of the product:

The Venezia chimney cap is particularly suitable for those interested in appearance as well as function. It gives adequate protection from water infiltration and wind.

Installation instructions:

Install on the terminal part of the chimney flue. Fix by means of a flue clamp. Do not use a silicon sealant only. Installation of the chimney cap must be carried out by qualified personnel.

STAINLESS
STEEL



COPPER



Available for Single Wall flue pipes, both male and female, and for Double Wall flue pipes 25mm insulation.

On request it is possible produce the cap for Double Wall with 50 mm insulation

Conforms to UNI 7129/01 sez. 4-3-3 regulations regarding chimney caps.

EC Certifications in conformity with EN 1856-1 :

- Resistance to flow
- Technical conformity report "Chimney cap protecting from rain" .

single wall - Art. 1275

ø	80	100	120	130	140	150	160	180	200	220	250	300	350	400
H	300	300	345	345	375	375	375	430	430	430	450	565	640	640
A	230	230	320	320	355	355	355	410	450	520	540	660	700	750
Hf	170	170	270	270	300	300	300	345	350	350	390	485	560	560

double wall - Art. 1275 DP

ø	80/130	100/150	130/180	150/200	180/230	200/250	250/300	300/350	350/400
H	345	375	430	430	430	450	565	640	640
A	320	355	410	450	520	540	660	700	750
Hf	270	300	345	350	350	390	485	560	560

